

## Write

SmartTemplate4 settings (en-US) ✕

Account:  ▶ Help

Use Common

✉ Write ✉ Reply ✉ Forward ℹ About

Write

Apply the following template to the new message:

Use HTML (e.g., <b>bold</b>)

Replace new-line with <br>

Debug mode

Contribute OK Zrušit

## Reply

SmartTemplate4 settings (en-US) ✕

Account:  ▶ Help

Use Common

✉ Write ✉ Reply ✉ Forward ℹ About

Reply

Apply the following template to the replied message:

```
<span style="font: 10pt Tahoma;">
<br>
----- Original message ----- <br>
<b>From:</b> %from% <br>
[[<b>To:</b> %to%]][[<br><b>Cc:</b> %cc%]] <br>
<b>Subject:</b> %subject% <br>
<b>Sent:</b> %X:=sent% %A%, %B% %d%, %Y% %1%:%M% %p(3)% <br>
</span>
```

Use HTML (e.g., <b>bold</b>)

Replace new-line with <br>

Use instead of default quote header

Debug mode

Contribute OK Zrušit

## Forward

SmartTemplate4 settings (en-US) ✕

Account: Common ▾ ▶ Help

Use Common

✉ Write ✉ Reply ✉ Forward ℹ About

**Forward**

Apply the following template to the forwarded message

```
<span style="font: 10pt Tahoma;">
<br>
----- Original message ----- <br>
<b>From:</b> %from% <br>
[[<b>To:</b> %to%]][[<br><b>Cc:</b> %cc%]] <br>
<b>Subject:</b> %subject% <br>
<b>Sent:</b> %X:=sent% %A%, %B% %d%, %Y% %l%:%M% %p(3)% <br>
<br>
</span>
```

Use HTML (e.g., <b>bold</b>)

Replace new-line with <br>

Disable default Thunderbird quote header

Debug mode

Contribute OK Zrušit